



OPIRA-H1100 / OPIRA-H1500 / OPIRA-H1800X Horizontal Laminar Flow Cabinets

opira.com.au



Accredited for compliance with ISO/IEC 17025-testing

Laminar flow cabinets prevent contamination of semiconductor wafers, pharmaceutical products, biological samples, and other particle sensitive materials.

The working area is protected from dust and airborne contaminants as filtered air is drawn through a HEPA filter and blown in a unidirectional (laminar) flow towards the user.

The workbench is made from stainless steel, so that it can be easily cleaned and less prone to corrosion.

The OPIRA-H1100 / OPIRA-H1500 / OPIRA-H1800X comes with a UV-C germicidal lamp and HEPA filter to sterilise the work area.

OPIRA-H1100 / OPIRA-H1500 / OPIRA-H1800X features:

- Designed and manufactured to comply with AS 2252.6-2011 Controlled environments Clean workstations - Design, installation & use
- Microprocessor control system - LED display
- 2 x waterproof sockets, located in the top panel for optimum convenience when using small devices inside the cabinet
- Transparent side glass windows maximise light



OPIRA BRISBANE
32 DIVIDEND STREET
MANSFIELD, QLD 4122

OPIRA MELBOURNE
25 GRAHAM ROAD
CLAYTON SOUTH, VIC 3169

OPIRA PERTH
9 EARLSTON PLACE
BOORAGOON, WA 6154

OPIRA SYDNEY
20 DUKE ST
FORESTVILLE, NSW 2087

CONTACT US

1300 157 969

SOLUTIONS@OPIRA.COM.AU

Model	OPIRA-H1100	OPIRA-H1500	OPIRA-H1800X
External size (W*D*H)	1100 x 808 x 1690mm	1500 x 808 x 1690mm	1800X X 808 X 1890mm
Internal size (W*D*H)	1000 x 500 x 600mm	1400 x 500 x 600mm	1700 x 500 x 800mm
Work Surface Height	750mm		
Display	LCD Display		
Air Velocity	Average of 0.3~0.5m/s		
Material	Main body: cold-rolled steel with anti-bacterial powder coating Work table: 304 stainless steel Side and front windows 5mm toughened glass, anti-UV (BBS-H1300-BBS-H1800) Side windows 8mm toughened glass, anti-UV (BBS-H1500)		
Pre-filter	Polyester fibre, washable		
HEPA Filter	99.999% efficiency at 0.3µm		
Noise	<65dB	<65dB	<65dB
LED Lamp	12W*1	16W*1	16W*2
UV Lamp	20W*1	30W*1	20W*2
	Emission of 253.7 nanometers		
Consumption	200W	300W	400W
Waterproof Socket	2 x total load ≤500W	2 x total load ≤500W	2 x total load ≤500W
Casters	Universal casters with leveling feet		
Power Supply	AC220V±10%, 50/60Hz		
Base Stand Height	675mm ±5mm	675mm ±5mm	680mm ±5mm
Standard Accessories	LED lamp, UV lamp x 2. base stand, waterproof socket x 2, hook x 10		
Optional Accessories	Electric height-adjustable base stand		
Gross Weight	175kg	216kg	255kg
Package Size (W*D*H)	1240 x 1050 x 1350mm	1650 x 1050 x 1350mm	1950 x 1050 x 1550mm



Our products have been designed and tested to comply with all applicable ACMA regulatory requirements and bear the RCM mark.



OPIRA BRISBANE
32 DIVIDEND STREET
MANSFIELD, QLD 4122

OPIRA MELBOURNE
25 GRAHAM ROAD
CLAYTON SOUTH, VIC 3169

OPIRA PERTH
9 EARLSTON PLACE
BOORAGOON, WA 6154

OPIRA SYDNEY
20 DUKE ST
FORESTVILLE, NSW 2087

CONTACT US
1300 157 969

SOLUTIONS@OPIRA.COM.AU