

Mobile Fume Extractor



INTRODUCTION

The mobile fume extractor is an air purification equipment which can provide the partial high pure environment. The airflow is vertical laminar flow type. It is widely used in medical research laboratories, precision instrument, bio-pharmacy, micro-organism studies and etc.

FEATURES

1. Freely moving, easy to operate and install.
2. The purification system consists of fan, primarily efficient filter, high efficient filter and activated carbon filter.
3. HEPA filter ensures the filtering efficiency to 99.999% efficiency at 0.3 μ m.

TECHNICAL PARAMETERS

Model	MFE-I
External Size(W*D*H)	500*500*980mm
Air Velocity	0.3~0.6m/s
Filter Efficiency	99.999% efficiency at 0.3 μ m
Noise	≤75dB(A)
Suction Inlet Diameter	375mm
Rated Power	180W
Power Supply	AC110/220V±10%, 50/60Hz
Gross Weight	15kg (Extracting arm) 61kg (Purification system)
Package Size(W*D*H)	810*510*600mm (Extracting arm) 630*630*1175mm (Purification system)

FFU (Fan Filter Unit)



FEATURES

1. FFU shell and HEPA filter adopt split design, easy to install and replace.
2. Microprocessor control system, energy-saving and low noise.
3. Long service-life blower, up to 100,000 hours, maintenance-free and small vibration.
4. Suitable for using separately or connecting together for assembly line.
5. Made of aluminium coated zinc plate, anti-corrosion, rust-proof and light weight.

TECHNICAL PARAMETERS

Model	FFU 1000	FFU 1200	FFU 1500	FFU 1800
External Size(W*D*H)	975*575*380mm	1175*575*380 mm	1475*575*380 mm	1775*575*380 mm
Air Velocity	0.45 m/s±20%			
HEPA Filter	99.999% efficiency at 0.3 μ m			
HEPA Filter Size(W*D*H)	970*69*570mm	1170*69*570mm	1470*69*570mm	1770*69*570mm
Blower	Built-in centrifugal blower			
Noise	≤60dB			
Consumption	110W		220W	
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 50/60Hz			
Shell Material	Aluminium coated zinc plate			
Gross Weight	60kg	70 kg	90kg	110kg
Package Size(W*D*H)	1135*540*800mm	1335*540*800mm	1635*540*800mm	1935*540*800mm